



Synthetic Blend SAE 5W-30 Motor Oil

SAMS1 SAE 5W-30 Synthetic Blend Motor Oil is a superior quality multi-grade motor oil designed for maximum engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. It is recommended for high-powered passenger cars, light trucks, sport utility vehicles and other mobile and stationary engines.

SAMS1 SAE 5W-30 Synthetic Blend Motor Oil is fully licensed to meet or exceed car manufacturers' ILSAC GF-5 and American Petroleum Institute (API) Resource Conserving SN service classifications and is backwards compatible with all earlier API classifications. SAMS1 SAE 5W-30 Synthetic Blend Motor Oil has been field tested to be comparable to American, European and Japanese manufacturers' requirements for: ACEA A1/B1 & A5/B5, WSS-M2C929A and WSS-M2C946A, Chrysler MS 6395, dexos, and GM 6094M as well as many other Ford, Honda, Mazda, Mitsubishi, GM and Chrysler vehicle requirements where a premium API SN synthetic blend motor oil is recommended.

Benefits and Applications

- API Resource Conserving SN and prior SM, SL, SJ Service Classifications
- ILSAC GF-5 Service Certification
- Lower pour point reduces start-up wear during cold weather
- Synthetic blend oil helps to improve fuel economy
- Compatible with conventional oils
- Excellent wear, corrosion, and rust protection
- Superior resistance to sludge and varnish deposit formation
- Designed with premium base stocks for added thermal breakdown resistance



Typical Characteristics - SAE 5W-30 Synthetic Blend

SAE GRADE		5W-30
API SERVICE		SN/GF-5
API Gravity	ASTM D287	32.5
Flash Point, COC °C/°F	ASTM D92	210/410
Pour Point, °C/°F	ASTM D97	-45/-49
Viscosity @ 40°C, cSt	ASTM D445	64.6
Viscosity @ 100°C, cSt	ASTM D445	10.8
Viscosity Index	ASTM D2270	159
CCS, mPa-sec, @ °C max	ASTM D5293	6600 @ -30
Phosphorus, wt% max	ASTM D4951	0.08
Total Base No. TBN	ASTM D2896	7.9

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

V151218



HANDLING AND SAFETY INFORMATION - Refer to SAMS1 (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.